



Saturated wood requires regular maintenance to preserve the both effectiveness of the protection and the appearance.

SATURATED WOOD CARE

FOREWORD / We recommend waiting one year after the installation of natural wood before applying a saturator to the dry wood to nourish and protect it. In fact, after the 4 seasons have passed, the pores are more open, this is the greying effect. / Applying a saturator after de-greying, will adhere better to the wood. It is strongly recommended to only apply saturator in fine weather, making sure no rain is forecast during the 48h following the application. / We recommend renewing these applications every 2 or 3 years depending on the exposure.

MAINTAIN		HOW TO PROCEED?
How do you keep the aesthetics of a saturated timber product?		/ The application of a maintenance coat of your saturated wood product colour will give a more intense colour / Renew every 1 to 2 years depending on the exposure / Without prior degreasing, clean using a soft cloth by applying a neutral detergent for wood / Apply one or more coats of saturator in your colour until the wood is soaked to bring back the shine
NATURAL ALTERATIONS	ORIGIN	HOW TO PROCEED?
DUST LAYERS	Natural and can accumulate on any materials used outdoors	/ Spray a neutral detergent for wood (Alternative: use a soft brush or a large non-abrasive sponge to rub the surface using neutral pH soap and hot water) / Wait a few moments, then rinse with clean water
MOSS STAINS	These are mainly caused by the exposure. They can appear as greenish stains	/ After cleaning, eventually apply one or more coats of saturator for your colour until the wood is soaked to bring back the shine
SUPERFICIAL SCRATCHES	Can be caused by everyday accidents (handles, pedals, garden tools, animal claws, etc.) handles, pedals, garden tools, animal claws, etc.)	/ Rub the scratched zone using a non-fluff cloth and a neutral detergent for wood / Leave to dry for at least 1h depending on the temperature / In dry weather, apply a first coat of saturator using a fine brush on the scratched zones / Leave to dry for 4h / Apply a second coat of saturator in the same way
CONSUMPTION Saturator repairs: 1L pot available in all colours Applicable surface area: about 7 m ² per coat per L		